



## SUGGESTED SPECIFICATIONS

### "STATIC" SYSTEM CURTAIN TYPE FIRE DAMPER

Furnish and install at all locations indicated on plans "**Static**" or "**Dynamic**" rated curtain fire dampers. The fire dampers shall be constructed of 22 gauge roll formed galvanized G90U steel, blade and frame. Each damper shall be constructed, tested and labeled in compliance with U.L. Standard 555, current edition. Each fire damper shall have an 1½ or 3 (as required) hourly fire protection rating. The fusible link shall be 165°F (212°F if required). The damper shall be labeled, as such, to refer to United Air's Installation Instructions. The fire damper shall be installed in walls/floors utilizing steel sleeves, retaining angles, and access doors as required by United Air's Installation Instructions, NFPA 90A, and local codes. Fire dampers shall be United Air or pre-approved equal.

#### Specify style of damper desired as follows:

**Type A**, Blades and frame in air stream.

**Type B**, Blades only out of air stream.

**Type CR**, Round high pressure - 100% free area - sealed

**Type CO**, Oval high pressure - 100% free area - sealed

**Type C**, Square/rectangular high pressure - 100% free area - sealed

**Type R**, Round low pressure - less than 100% free area - unsealed

**Type DR**, Round low pressure - 100% free area - unsealed

**Type DO**, Oval low pressure - 100% free area - unsealed

**Type D**, Square/rectangular low pressure - 100% free area - unsealed

**Type OW**, Type "A" damper approved for out of wall installations

#### LEADER'S MODELS

Model **105** - Thinline (2"): 1½ hour rated, horizontal/vertical mounted

**110** - Thinline (2¾"): 1½ hour rated, horizontal/vertical mounted.

**115** - Thinline (2"): 1½ hour rated, vertical mounted

**120** - Thinline (2¾"): 1½ hour rated, vertical mounted.

**205** - Standard 1½ hour rated, horizontal/vertical mounted.

**207** - Stainless steel, 1½ hour rated, horizontal/vertical mounted.

**215** - Standard 1½ hour rated, vertical mounted.

**255** - Standard 3 hour rated, vertical mounted.

**277** - Stainless steel, 1½ hour rated, vertical mounted.

**305** - Wide blade (6"): 1½ hour rated, horizontal/vertical mounted.

**315** - Wide blade (6"): 1½ hour rated, vertical mounted.

**350** - Largest single section 1½ hour rated, vertical mounted on the market. 3-2001



Mailing Address:

P.O. Box 40913

Nashville, Tennessee 37204

PHONE: 615-256-3500

Business Address:

2509 Cruzan Street

Nashville, Tennessee 37211

FAX: 800-388-3806

DIVISION OF LEADER INDUSTRIES, INC.