

ACTUATORS FOR 600 / ASMD SERIES

LEADER DAMPER ACTUATORS	MAXIMUM DAMPER SIZE	ACTUATOR RATING ELECTRIC OR PNEUMATIC	MAXIMUM TEMP.	MOUNTING INTERNAL OR EXTERNAL
ML-4115 Honeywell	24"w X 10"h	Electric .18A – 120 VAC	250 F	Internal or External
ML-8115 Honeywell	24"w X 10"h	Electric 16 VA – 24 VAC	250 F	Internal or External
MS-4309 Honeywell	36"w X 36"h	Electric .25A – 120 VAC	350 F	Internal or External
MS-4209 Honeywell	36"w X 36"h	Electric .25A – 120 VAC	350 F	Internal or External
MS-8309 Honeywell	36"w X 36"h	Electric 23 VA – 24 VAC	350 F	Internal or External
MS-8209 Honeywell	36"w X 36"h	Electric 23 VA – 24 VAC	350 F	Internal or External
GGD-221.1U Siemens	36"w X 48"h	Electric – 120 VAC 1.3 A running .09 A holding	350 F	Internal or External
GGD-121.1U Siemens	36"w X 48"h	Electric – 24 VAC 6.3 A running .42 A holding	350 F	Internal or External
MS-4120 Honeywell	36"w X 48"h 72"w X 36"h	Electric .35A – 120 VAC	350 F	Internal or External
MS-8120 Honeywell	36"w X 48"h 72"w X 36"h	Electric 45 VA – 24 VAC	350 F	Internal or External
331-4826 Siemens	36"w X 36"h	Pneumatic 20 psi	350 F	Internal or External
331-2961 Siemens	36"w X 48"h	Pneumatic 22 psi	350 F	Internal or External
Honeywell 4202	12"w X 12" h	Electric 120 VAC	250 F	External

ACTUATORS FOR 600 / ASMD SERIES (cont'd)

Honeywell 4302	12"w X 12"h	Electric 120 VAC	250 F	Internal
Honeywell 8202	12"w X 12"h	Electric 24 VAC	250 F	External
Honeywell 8302	12"w X 12"h	Electric 24 VAC	250 F	Internal