

United Air's Model	CSFM Listing No.	California State Fire Marshal Classification	U.L. Standard	U.L. File	Underwriters Laboratories Classification	Maximum Single Section
CFD-1	3225-273:101	3 Hr. Ceiling Rad. Damper	UL 555 C	R 12274	4 Hr. Ceiling Rad. Damper- Sq.	24"w x 24"l
CFD-2	3225-273:101	1 Hr. Ceiling Rad. Damper	UL 555 C	R 12274	2 Hr. Ceiling Rad. Damper- Sq.	24"w x 24"l
CFD-R	3225-273:101	3 Hr. Ceiling Rad. Damper	UL 555 C	R 12274	4 Hr. Ceiling Rad. Damper- Rd.	24" Dia.
CFD-H	3225-273:101	3 Hr. Ceiling Rad. Damper	UL 555 C	R 12274	4 Hr. Ceiling Rad. Damper- Sq.	24"w x 24"l
105	N / A	Horizontal Fire Damper	UL 555	R 5543	1 1/2 Hr. Horz. Thin. Fire Damper	36"w x 36"h
110	N / A	Horizontal Fire Damper	UL 555	R 5543	1 1/2 Hr. Horz. Thin. Fire Damper	36"w x 36"h
115	3225-273:100	1 1/2 Hr. Fire Damper	UL 555	R 5543	1 1/2 Hr. Vert. Thin. Fire Damper	48"w x 48"h
120	3225-273:100	1 1/2 Hr. Fire Damper	UL 555	R 5543	1 1/2 Hr. Vert. Thin. Fire Damper	48"w x 48"h
205	N / A	Horizontal Fire Damper	UL 555	R 5543	1 1/2 Hr. Horz/Vert. Fire Damper	40"w x 40"h
207	N / A	Horizontal Fire Damper	UL 555	R 5543	1 1/2 Hr. Hor/Ver S.S. Fire Damper	36"w x 36"h
215	3225-273:100	1 1/2 Hr. Fire Damper	UL 555	R 5543	1 1/2 Hr. Vert. Fire Damper	52"w x 52"h
255	3225-273:100	3 Hr. Fire Damper	UL 555	R 5543	3 Hr. Vert. Fire Damper	52"w x 52"h
277	3225-273:100	1 1/2 Hr. Fire Damper SS	UL 555	R 5543	1 1/2 Hr. Vert. S.S. Fire Damper	48"w x 48"h
305	3225-273:104	1 1/2 Hr. Fire Damper WB	UL 555	R 5543	1 1/2 Hr. Hor/Ver. WB Fire Damper	36"w x 36"h
315	3225-273:104	1 1/2 Hr. Fire Damper WB	UL 555	R 5543	1 1/2 Hr. Vert. WB Fire Damper	48"w x 48"h
350	3225-273:005	1 1/2 Hr. Fire Damper	UL 555	R 5543	1 1/2 Hr. Vert. Fire Damper	120"w x 120"h
SMD-1	3230-273:103	Leakage Rated - Class 1	UL 555 S	R 12271	Leakage Rated - Class 1 - Crimp	36"w x 48"h
SMD-2	3230-273:103	Leakage Rated - Class 2	UL 555 S	R 12271	Leakage Rated - Class 2 - Crimp	36"w x 48"h
SMD-3	3230-273:103	Leakage Rated - Class 3	UL 555 S	R 12271	Leakage Rated - Class 3 - Crimp	36"w x 48"h
ASMD-1	3230-273:103	Leakage Rated - Class 1	UL 555 S	R 5543	Leakage Rated - Class 1 - Airfoil	36"w x 48"h
ASMD-2	3230-273:103	Leakage Rated - Class 2	UL 555 S	R 5543	Leakage Rated - Class 1 - Airfoil	36"w x 48"h
501	3225-273:106 3230-273:110	1-1/2 Hr FD / Leakage Class 1	UL 555 / UL 555 S	R 5543	1-1/2 Hr FD / Leakage Class 1 - Crimp	36"w x 48"h
502	3225-273:106 3230-273:110	1-1/2 Hr FD / Leakage Class 2	UL 555 / UL 555 S	R 5543	1-1/2 Hr FD / Leakage Class 2 - Crimp	36"w x 48"h
503	3225-273:106 3230-273:110	1-1/2 Hr FD / Leakage Class 3	UL 555 / UL 555 S	R 5543	1-1/2 Hr FD / Leakage Class 3 - Crimp	36"w x 48"h
505	3225-273:106	1 1/2 Hr. Fire Damper	UL 555	R 5543	1 1/2 Hr. Horz/Vert. Fire Damper	36"w x 48"h
CD-501	3225-273:105 3230-273:107	1Hr Corr.Dam / Leakage Class 1	UL 555 / UL 555 S	R 16105	1 Hr Corr.Damp / Leakage Class 1-Crimp	24"w x 24"h
CD-502	3225-273:105 3230-273:107	1Hr Corr.Dam / Leakage Class 2	UL 555 / UL 555 S	R 16105	1 Hr Corr.Damp / Leakage Class 2-Crimp	24"w x 24"h
601	3225-273:108 3230-273:109	1-1/2 Hr FD / Leakage Class 1	UL 555 / UL 555 S	R 5543	1-1/2 Hr FD / Leakage Class 1 - Airfoil	36"w x 48"h
602	3225-273:108 3230-273:109	1-1/2 Hr FD / Leakage Class 2	UL 555 / UL 555 S	R 5543	1-1/2 Hr FD / Leakage Class 1 - Airfoil	36"w x 48"h
605	3225-273:108	1 1/2 Hr. Fire Damper	UL 555	R 5543	1 1/2 Hr. Horz/Vert. Fire Damper	36"w x 48"h

United Air offers a wide variety of fire protection products to meet your design requirements. We have had these products tested and approved by Underwriters Laboratories(UL), as well as evaluated and approved by the California State Fire Marshall. We give you the assurance that our products provides the necessary fire protection to keep society safe. Our goal is not to push the edge, but to leave some for a safety factor.